Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (cancelled)
- 2. (currently amended) The article recited in Claim 25 [[1]] wherein said adhesive layer forms a strip around said flange outer surface.
- 3. (currently amended) The article recited in Claim 25 [[1]] wherein said adhesive layer covers said flange outer surface.
- 4. (currently amended) The article recited in Claim 25 [[1]] wherein said fastener has a substantially circular cross-section.
- 5. (withdrawn) The article recited in Claim 1 wherein said fastener has a hexagonal cross-section.
- 6. (currently amended) The article recited in Claim 25 [[1]] wherein said outer surface further comprises at least one ridge.
- 7. (cancelled)
- 8. (cancelled)
- 9. (withdrawn) The article recited in Claim 1 wherein said outer surface further comprises a knurled portion.
- 10. (withdrawn) The article recited in Claim 9 wherein said adhesive layer is located on said knurled portion of said outer surface.

Attorney Docket No. SHXP:101US U.S. Patent Application No. 10/605,729 Reply to Office Action of June 29, 2005

Date: September 22, 2005

- 11. (withdrawn) The article recited in Claim 10 wherein said adhesive layer covers said knurled portion.
- 12. (currently amended) The article recited in Claim 25 [[1]] wherein said adhesive layer comprises a threadlocking composition.
- 13. (original) The article recited in Claim 12 wherein said threadlocking composition comprises methacrylate ester.
- 14. (original) The article recited in Claim 12 wherein said threadlocking composition comprises an epoxy.
- 15. (currently amended) The article recited in Claim 25 [[1]] wherein a portion of said inner surface is threaded.
- 16. (cancelled)
- 17. (cancelled)
- 18. (currently amended) The article recited in Claim <u>25</u> 16 wherein said flange comprises a knurled portion.
- 19. (original) The article recited in Claim 18 wherein said knurled portion of said flange has adhesive thereon.
- 20. (currently amended) The article recited in Claim <u>25</u> [[1]] further comprising a stud.
- 21. (withdrawn) The article recited in Claim 1 wherein said outer surface comprises
- at least one slot.
- 22. (currently amended) The article recited in Claim <u>25</u> [[1]] wherein said adhesive is enclosed in microcapsules.

Attorney Docket No. SHXP:101US. U.S. Patent Application No. 10/605,729 Reply to Office Action of June 29, 2005

Date: September 22, 2005

- 23. (currently amended) The article recited in Claim 25 [[1]] wherein said fastener has a closed end.
- 24. (currently amended) The article recited in Claim <u>25</u> [[1]] wherein said fastener has an open end.
- 25. (previously presented) An article for fastening comprising:

a fastener selected from the group including a rivet nut, a rivet nut stud, a threaded insert, and a blind threaded insert, wherein said fastener has an inner surface, an outer surface, and a flange and at least a portion of a surface of said flange has an adhesive thereon.